



### Stock list Bochum

Seamless steel pipes, EN 10216-1, P235TR2, R/L 5-7 m, plain ends

| OD    |   | WT   |    | black | AGI Q151 | 40 my red-brown | all RAL-colours powder-coated |
|-------|---|------|----|-------|----------|-----------------|-------------------------------|
| 21,3  | x | 2,0  | mm | ✓     | +        | +               | +                             |
| 25,0  | x | 2,0  | mm | ✓     | +        | +               | +                             |
| 26,9  | x | 2,3  | mm | ✓     | +        | +               | +                             |
| 30,0  | x | 2,6  | mm | ✓     | +        | +               | +                             |
| 31,8  | x | 2,6  | mm | ✓     | +        | +               | +                             |
| 33,7  | x | 2,6  | mm | ✓     | +        | +               | +                             |
| 42,4  | x | 2,6  | mm | ✓     | ✓        | +               | +                             |
| 44,5  | x | 2,6  | mm | +     | +        | +               | +                             |
| 48,3  | x | 2,6  | mm | ✓     | ✓        | +               | +                             |
| 57,0  | x | 2,9  | mm | ✓     | ✓        | +               | +                             |
| 60,3  | x | 2,9  | mm | ✓     | ✓        | ✓               | +                             |
| 63,5  | x | 2,9  | mm | +     | +        | +               | +                             |
| 70,0  | x | 2,9  | mm | ✓     | +        | +               | +                             |
| 76,1  | x | 2,9  | mm | ✓     | ✓        | ✓               | +                             |
| 82,5  | x | 3,2  | mm | ✓     | +        | +               | +                             |
| 88,9  | x | 3,2  | mm | ✓     | ✓        | ✓               | +                             |
| 101,6 | x | 3,6  | mm | ✓     | +        | +               | +                             |
| 108,0 | x | 3,6  | mm | ✓     | +        | +               | +                             |
| 114,3 | x | 3,6  | mm | ✓     | ✓        | ✓               | +                             |
| 121,0 | x | 4,0  | mm | ✓     | +        | +               | +                             |
| 133,0 | x | 4,0  | mm | ✓     | +        | +               | +                             |
| 139,7 | x | 4,0  | mm | ✓     | ✓        | ✓               | +                             |
| 152,4 | x | 4,5  | mm | ✓     | +        | +               | +                             |
| 159,0 | x | 4,5  | mm | ✓     | ✓        | +               | +                             |
| 168,3 | x | 4,5  | mm | ✓     | ✓        | ✓               | +                             |
| 177,8 | x | 5,0  | mm | ✓     | +        | +               | +                             |
| 193,7 | x | 5,6  | mm | ✓     | +        | +               | +                             |
| 219,1 | x | 6,3  | mm | ✓     | ✓        | ✓               | +                             |
| 244,5 | x | 6,3  | mm | ✓     | +        | +               | +                             |
| 273,0 | x | 6,3  | mm | ✓     | ✓        | +               | +                             |
| 323,9 | x | 7,1  | mm | ✓     | ✓        | +               | +                             |
| 355,6 | x | 8,0  | mm | ✓     | +        | +               | +                             |
| 406,4 | x | 8,8  | mm | ✓     | +        | +               | +                             |
| 457,0 | x | 10,0 | mm | ✓     | +        | +               | +                             |
| 508,0 | x | 11,0 | mm | ✓     | +        | +               | +                             |
| 610,0 | x | 12,5 | mm | +     | +        | +               |                               |

✓ = from stock

+ = on demand



### Stock list Bochum

Welded steel pipes, EN 10217-1, P235TR1, R/L approx. 6 m, plain ends

| OD    |   | WT     |  | black | AGI Q151 |
|-------|---|--------|--|-------|----------|
| 33,7  | x | 2,6 mm |  | +     | +        |
| 42,4  | x | 2,3 mm |  | ✓     | +        |
|       | x | 2,6 mm |  | ✓     | +        |
| 48,3  | x | 2,3 mm |  | ✓     | ✓        |
|       | x | 2,3 mm |  | ✓     | ✓        |
| 60,3  | x | 2,6 mm |  | ✓     | +        |
|       | x | 2,9 mm |  | ✓     | +        |
|       | x | 2,6 mm |  | ✓     | ✓        |
| 76,1  | x | 2,9 mm |  | ✓     | +        |
|       | x | 2,6 mm |  | ✓     | ✓        |
| 88,9  | x | 2,9 mm |  | ✓     | ✓        |
|       | x | 3,2 mm |  | ✓     | +        |
|       | x | 3,2 mm |  | ✓     | ✓        |
| 114,3 | x | 3,2 mm |  | ✓     | ✓        |
|       | x | 3,6 mm |  | ✓     | +        |
| 139,7 | x | 3,6 mm |  | ✓     | ✓        |
|       | x | 4,0 mm |  | ✓     | +        |
|       | x | 3,6 mm |  | ✓     | ✓        |
| 168,3 | x | 4,0 mm |  | ✓     | ✓        |
|       | x | 4,5 mm |  | ✓     | +        |
| 219,1 | x | 4,5 mm |  | ✓     | ✓        |
|       | x | 6,3 mm |  | ✓     | +        |
| 273,0 | x | 5,0 mm |  | ✓     | ✓        |
| 323,9 | x | 5,6 mm |  | ✓     | ✓        |
| 355,6 | x | 5,6 mm |  | ✓     | +        |
| 406,4 | x | 6,3 mm |  | ✓     | +        |
| 508,0 | x | 6,3 mm |  | ✓     | +        |
| 610,0 | x | 6,3 mm |  | +     | +        |

✓ = from stock

+ = on demand



### Stock list Bochum

Welded steel pipes, R/L approx. 6 m grooved on both sides

| OD    | WT |        | Steel pipes EN 10217-1, P235TR1 |          |          |
|-------|----|--------|---------------------------------|----------|----------|
|       |    |        | galvanized                      | RAL 3000 | RAL 9010 |
| 42,4  | x  | 2,6 mm | ✓                               | ✓        | ✓        |
| 48,3  | x  | 2,6 mm | ✓                               | ✓        | ✓        |
| 60,3  | x  | 2,6 mm | ✓                               | ✓        | +        |
| 76,1  | x  | 2,6 mm | ✓                               | ✓        | ✓        |
|       |    | 2,9 mm | ✓                               | ✓        | ✓        |
| 88,9  | x  | 2,9 mm | ✓                               | ✓        | ✓        |
| 114,3 | x  | 3,2 mm | ✓                               | ✓        | ✓        |
| 139,7 | x  | 3,6 mm | ✓                               | ✓        | ✓        |
| 168,3 | x  | 4,0 mm | ✓                               | ✓        | ✓        |
| 219,1 | x  | 4,5 mm | ✓                               | ✓        | ✓        |
| 273,0 | x  | 5,0 mm | ✓                               | ✓        | +        |
| 323,9 | x  | 5,6 mm | ✓                               | ✓        | +        |

| Inch   | Dimension  |    | Threaded pipes EN 10255-M, S195T |          |          |
|--------|------------|----|----------------------------------|----------|----------|
|        |            |    | galvanized                       | RAL 3000 | RAL 9010 |
| 1 1/4" | 42,4 x 3,2 | mm | ✓                                | ✓        | ✓        |
| 1 1/2" | 48,3 x 3,2 | mm | ✓                                | ✓        | ✓        |
| 2"     | 60,3 x 3,6 | mm | ✓                                | ✓        | ✓        |

✓ = from stock

+ = on demand



### Stock list Bochum

Boiler Tube, P235GH TC1, black, plain ends

| OD    | WT |         | seamless R/L 5-7 m | welded R/L approx. 6 m |
|-------|----|---------|--------------------|------------------------|
|       |    |         | EN 10216-2         | EN 10217-2             |
| 21,3  | x  | 2,0 mm  | ✓                  | +                      |
| 25,0  | x  | 2,0 mm  | ✓                  | +                      |
| 26,9  | x  | 2,3 mm  | ✓                  | +                      |
| 30,0  | x  | 2,6 mm  | ✓                  | +                      |
| 33,7  | x  | 2,6 mm  | ✓                  | +                      |
| 42,4  | x  | 2,6 mm  | ✓                  | +                      |
| 48,3  | x  | 2,6 mm  | ✓                  | +                      |
| 57,0  | x  | 2,9 mm  | +                  | +                      |
| 60,3  | x  | 2,9 mm  | ✓                  | +                      |
| 70,0  | x  | 2,9 mm  | ✓                  | +                      |
| 76,1  | x  | 2,9 mm  | ✓                  | +                      |
| 82,5  | x  | 3,2 mm  | ✓                  | +                      |
| 88,9  | x  | 3,2 mm  | ✓                  | +                      |
| 101,6 | x  | 3,6 mm  | ✓                  | +                      |
| 108,0 | x  | 3,6 mm  | ✓                  | +                      |
| 114,3 | x  | 3,6 mm  | ✓                  | +                      |
| 133,0 | x  | 4,0 mm  | ✓                  | +                      |
| 139,7 | x  | 4,0 mm  | ✓                  | +                      |
| 159,0 | x  | 4,5 mm  | ✓                  | +                      |
| 168,3 | x  | 4,0 mm  | +                  | ✓                      |
|       |    | 4,5 mm  | ✓                  | +                      |
| 193,7 | x  | 5,6 mm  | ✓                  | +                      |
| 219,1 | x  | 4,5 mm  | +                  | ✓                      |
|       |    | 6,3 mm  | ✓                  | +                      |
| 244,5 | x  | 6,3 mm  | ✓                  | +                      |
| 273,0 | x  | 5,0 mm  | +                  | ✓                      |
|       |    | 6,3 mm  | ✓                  | +                      |
| 323,9 | x  | 5,6 mm  | +                  | ✓                      |
|       |    | 7,1 mm  | ✓                  | +                      |
| 355,6 | x  | 5,6 mm  | +                  | ✓                      |
|       |    | 8,0 mm  | ✓                  | +                      |
| 406,4 | x  | 6,3 mm  | +                  | ✓                      |
|       |    | 8,8 mm  | ✓                  | +                      |
| 457,0 | x  | 10,0 mm | ✓                  | +                      |
| 508,0 | x  | 6,3 mm  | +                  | ✓                      |
|       |    | 11,0 mm | ✓                  | +                      |

✓ = from stock

+= on demand



### Stock list Bochum

Seamless threaded pipes, EN 10255-M, S195T, R/L 5-7 m, plain ends

| Inch             | Dimension   |    | black | galvanized | AGI Q151 | 40 my red-brown |
|------------------|-------------|----|-------|------------|----------|-----------------|
| $\frac{1}{4}$ "  | 13,2 x 2,3  | mm | ✓     | +          | +        | +               |
| $\frac{3}{8}$ "  | 17,2 x 2,3  | mm | ✓     | +          | +        | +               |
| $\frac{1}{2}$ "  | 21,3 x 2,6  | mm | ✓     | ✓          | ✓        | ✓               |
| $\frac{3}{4}$ "  | 26,9 x 2,6  | mm | ✓     | ✓          | ✓        | ✓               |
| 1"               | 33,7 x 3,2  | mm | ✓     | ✓          | ✓        | ✓               |
| $1\frac{1}{4}$ " | 42,4 x 3,2  | mm | ✓     | ✓          | ✓        | ✓               |
| $1\frac{1}{2}$ " | 48,3 x 3,2  | mm | ✓     | ✓          | ✓        | ✓               |
| 2"               | 60,3 x 3,6  | mm | ✓     | ✓          | ✓        | ✓               |
| $2\frac{1}{2}$ " | 76,1 x 3,6  | mm | ✓     | ✓          | +        | +               |
| 3"               | 88,9 x 4,0  | mm | ✓     | ✓          | +        | +               |
| 4"               | 114,3 x 4,5 | mm | ✓     | ✓          | +        | +               |

Welded threaded pipes, EN 10255-M, S195T, R/L approx. 6 m, plain ends

| Inch             | Dimension   |    | black | galvanized | AGI Q151 | RAL 3000 | RAL 9010 |
|------------------|-------------|----|-------|------------|----------|----------|----------|
| $\frac{3}{8}$ "  | 17,2 x 2,3  | mm | ✓     | ✓          | +        | +        | +        |
| $\frac{1}{2}$ "  | 21,3 x 2,6  | mm | ✓     | ✓          | ✓        | +        | +        |
| $\frac{3}{4}$ "  | 26,9 x 2,6  | mm | ✓     | ✓          | ✓        | +        | +        |
| 1"               | 33,7 x 3,2  | mm | ✓     | ✓          | ✓        | ✓        | ✓        |
| $1\frac{1}{4}$ " | 42,4 x 3,2  | mm | ✓     | ✓          | ✓        | ✓        | +        |
| $1\frac{1}{2}$ " | 48,3 x 3,2  | mm | ✓     | ✓          | ✓        | ✓        | +        |
| 2"               | 60,3 x 3,6  | mm | ✓     | ✓          | ✓        | ✓        | +        |
| $2\frac{1}{2}$ " | 76,1 x 3,6  | mm | ✓     | ✓          | +        | +        | +        |
| 3"               | 88,9 x 4,0  | mm | +     | ✓          | +        | +        | +        |
| 4"               | 114,3 x 4,5 | mm | +     | ✓          | +        | +        | +        |

✓ = from stock

+ = on demand



### **Stock list Bochum**

Welded threaded pipes, EN 10255, S195T, row L, R/L 5-7 m, plain ends

| Inch   | Dimension   |    | black | galvanized |
|--------|-------------|----|-------|------------|
| 1/2"   | 21,3 x 2,3  | mm | ✓     | ✓          |
| 3/4"   | 26,9 x 2,3  | mm | ✓     | ✓          |
| 1"     | 33,7 x 2,9  | mm | ✓     | ✓          |
| 1 1/4" | 42,4 x 2,9  | mm | ✓     | ✓          |
| 1 1/2" | 48,3 x 2,9  | mm | ✓     | +          |
| 2"     | 60,3 x 3,2  | mm | ✓     | ✓          |
| 2 1/2" | 76,1 x 3,2  | mm | ✓     | +          |
| 3"     | 88,9 x 3,2  | mm | ✓     | ✓          |
| 4"     | 114,3 x 3,6 | mm | ✓     | ✓          |

*Please also send us your requests and needs  
for prefabrication, processing, coatings etc.  
that are not included in this list.*